EP1020r

10.4" EPOSTER All-IN-ONE COMMERCIAL DISPLAY

Perfect Size for Up Close, High Impact Messaging

ViewSonic's EP1020r wireless display is just right for POS messaging or meeting room schedules. It features a built-in media player with internal storage capable of playing of JPEG images and video content with audio. Vivid retail messaging is easily configured via a play list, using the included Signage Manager Express Software and uploaded into the EP1020r display over a corporate network or manually using a USB thumb drive. Great for advertising in high visibility locations, informational signs for hotel lobbies and public locations, even for advertising boards in banks and on university campuses. The EP1020r is also SMIL compatible making the perfect companion for ViewSonic's new ScheduleIT software for automated meeting room scheduling.

- **10.4" wireless display with integrated media player**
- **800x600 display resolution**
- **250 nits of brightness with 400:1 contrast ratio**
- **Signage Manager Express**
  Content scheduling and management software – MS Windows compatible
- **Supports photos**
  Video music and Text – JPEG, MPEG 1, MPEG-4ASP, DivX, BMP
- **Easy loading of content through USB or Network (RJ45) Ethernet**
- **Built in 3W x2 audio**
- **Compatible with ViewSonic Schedule IT automated meeting room scheduling software**

ViewSonic®
See the difference®

EP1020r

10.4" EPOSTER ALL-IN-ONE COMMERICAL DISPLAY

DISPLAY	Diagonal	10.4" (4:3) TFT LCD
	Resolution	800x600 dots
	Color	Over 16.7M color (depending on video card used)
	Brightness	250 cd/m² (typ)
	Contrast Ratio	400:1 (typ)
	Response Time	8ms (typ gray-to-gray)
	View Angle	Up and down 178°, left and right 178° (typ) @ CR>10
CONNECTIVITY	Ethernet	RJ45 (10/100M)
	Storage	2GB Compact Flash
	USB	1.1 (x1)
FILE FORMATS	Music	LPCM, sampling rate: 32–48KHZ/16–24 bit
		MPEG1 Layer 3, sampling rate: 32–48KHZ, bit rate: 32–320Kbps
	Photo	JPEG baseline 5120x3840, progressive 2048x1536
AUDIO	Speakers	3W (x2)
CONTENT MANAGEMENT	Software	Signage Manager Express
	Operating System	MS Windows
POWER	Supply	3.2–1.38 A @ 100–240VAC, 50/60Hz
	Consumption	Max 24W
	Save	Off < 1W
OPERATING CONDITIONS	Temperature	32–122° F (0–40° C)
	Humidity	5–85% (non-condensing)
STORAGE ENVIRONMENT	Temperature	0–40° F (32°–122° C)
	Humidity	10–90% (non-condensing)
DIMENSIONS (WxHxD)	Physical	9.9" x 7.8" x 1.7" (251mm x 198mm x 43mm)
WEIGHT	Net	4.0 lbs. (1.8 kg)
	Gross	5.3 lbs. (2.4 kg)
WALL MOUNT		75mm x 75mm
REGULATIONS		FCC, ICES 003, CE
MTBF		50,000 hrs.
PACKAGE CONTENTS		ePoster, AC adapter, stand, antenna, Quick Start Guide and Software on CD

1 – Stylish Glossy Design
2 – SD/MS (Storage)
3 – Service Port
4 – USB
5 – Ethernet RJ45
6 – Headphone Jack
7 – Power On/Off

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

Microsoft, Windows, and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries. Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2011 ViewSonic Corporation. All rights reserved. [15529-02B-08/11] EP1020r

ViewSonic® See the difference®

For more product information, visit us on the web at ViewSonic.com